

SOUNDWALL™ X-BASE AW

ALL-WEATHER ARCHITECTURAL SPEAKERS



The SoundWall™ X-Base 600/800 All-weather in-ceiling and in-wall speakers deliver Morel's iconic sound performance in a highly humid and wet environment.

KEY FEATURES

- 2-way and coaxial speaker design for custom integration installations
- All-weather (IP54 rated) speaker solution for high humidity and wet locations
- Excellent high-frequency off-axis dispersion
- Great tonal balance with rich and dynamic bass
- Highly efficient speaker design - over 90dB
- Paintable frameless grilles, round and square options available
- Easy to install



XBW600 AW



XBC600 AW



XBC800 AW

Drive units	Woofer: 6.5" Tweeter: 1" soft dome	Woofer: 6.5"	Woofer: 8"
Nominal impedance	4 ohm	4 ohm	4 ohm
Sensitivity 2.83V/1M	90 dB	90 dB	91.5 dB
Power handling	90W(RMS)	80W(RMS)	100W(RMS)
Frequency response	50-22,000Hz (-5dB)	55-20,000Hz (-5dB)	45-20,000Hz (-5dB)
Grille	All weather stainless steel, paintable mesh grille with E-coating	All weather stainless steel, paintable mesh grille with E-coating	All weather stainless steel, paintable mesh grille with E-coating
Exterior grille dimension	8.4" x 11.8" (212x300mm)	Ø 8.9" (228mm)	Ø 11.1" (282mm)
Cut out dimensions	7.3" x 10.7" (185x273mm)	Ø 8.1" (206mm)	Ø 9.7" (246mm)
Mounting depth	3.15" (85mm)	3.15" (85mm)	3.9" (100mm)
Grille finish	White	White	White

* Morel operates a policy of continuous product design improvement, consequently, specifications are subject to alteration without prior notice.



unleash the music
www.morelhifi.com

