



## LCR 4 DRIVERS SPECIFICATIONS

	INTEGRA 4'' IC-4M I	BASS/SUB 4'' IC-4M W	4'' COAX IC4X
Master Crossover	180Hz 6dB highpass, 150Hz 12dB lowpass (available only in master unit)	Parallel connection, 4 ohm impedance	4,500Hz / 6dB
Drive units	<b>Integra:</b> 4'' driver with 2.1'' high temperature aluminum Hexatech™ voice coil, neodymium magnet motor. <b>Tweeter:</b> 1½'' (28mm) soft dome, driven by a neodymium magnet motor	4'' driver with 2.1'' high temperature aluminum voice coil, neodymium magnet motor, high lowercase ±6mm	<b>Woofers:</b> 4'' paper composite cellular fiber cone, 1.1" voice coil, ferrite magnet motor. <b>Tweeter:</b> 1" soft dome, neodymium magnet motor.
Nominal impedance	4 ohm	4 ohm	4 ohm
Sensitivity 2.83V/1M	88dB	84dB	87.5dB
Power handling	80W (RMS)	80W (RMS)	45W (RMS)
Weight	0.4Kg (0.97lbs)	0.56Kg (1.23lbs)	0.76Kg (1.67lbs)
Crossover	2,300Hz 12dB		
Frequency response	100-20,000Hz (±3dB)	40-3000Hz (±3dB)	75-20,000Hz
Overall dimensions (D,H)	5.3Ø ,3.15" (135Ø ,80mm)	5.3Ø ,3.15" (135Ø ,80mm)	5.3Ø ,3.15" (135Ø ,80mm)
Cut Out Dimensions	Ø125mm (4.92'')	125mm (4.92'')	125mm (4.92'')
Mounting Depth	85mm (3.34'')	85mm (3.34'')	85mm (3.34'')
Finish	White	White	White