



Tempo Ultra- 2 way

Two way system		Tempo 502	Tempo 602	Tempo 572	Tempo 692
Nominal Impedance		4 ohm	4 ohm	4 ohm	4 ohm
Power Handling		100W	120W	110W	130W
Max. Transient Power Handling		250W	250W	250W	280W
Sensitivity (2.83V/1M)		89db	90db	90db	91db
Frequency Response		65-22000	55-22000Hz	60-22000Hz	50-22000Hz
Voice Coil Diameter	Woofers:	38 mm (1.50")	38 mm (1.50")	38 mm (1.50")	38 mm (1.50")
	Tweeters:	28 mm (1.125")	28 mm (1.125")	28 mm (1.125")	28 mm (1.125")
Voice Coil Wire	Woofers:	Copper	Copper	Copper	Copper
	Tweeters:	Copper	Copper	Copper	Copper
Magnet System	Woofers:	high-grade ferrite	high-grade ferrite	high-grade ferrite	high-grade ferrite
	Tweeters:	Neodymium	Neodymium	Neodymium	Neodymium
Mounting Depth	Woofers:	57 mm (2.25")	64 mm (2.52")	62 mm (2.45")	85 mm (3.35")
	Tweeters:	20 mm (0.80)	20 mm (0.80)	20 mm (0.80)	20 mm (0.80)